

CLASSIC

TRADITIONAL COLLECTION - PAVERS & SLABS



Classic pavers are manufactured to exceed ASTM standards for quality and strength. Available in a variety of shapes and sizes, these products utilize a traditional product mix of large and small aggregates, that is consistent from top to bottom, with color mixed throughout. The result is a traditional, smooth surface texture.



CLASSIC

STANDARD SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
24 x 48"	23 ¹³ / ₁₆ x 47 ⁷ / ₈ "	604.8 x 1214.4mm	2 ¹ / ₂ " (63.5mm)
24 x 36" *Available with a false groove at 24"	23 ¹³ / ₁₆ x 35 ¹³ / ₁₆ "	604.8 x 909.6mm	2" (51mm)
24 x 24"	23 ¹³ / ₁₆ x 23 ¹³ / ₁₆ "	604.8 x 604.8mm	2" (51mm)
18 x 36"	17 ¹³ / ₁₆ x 35 ¹³ / ₁₆ "	452.4 x 909.6mm	2" (51mm)
18 x 24"	17 ¹³ / ₁₆ x 23 ¹³ / ₁₆ "	452.5 x 604.8mm	2" (51mm)
15 x 30"	15 x 29 ⁷ / ₈ "	375 x 750mm	2 ³ / ₈ " (60mm)
12 x 24"	11 ⁷ / ₈ x 23 ¹³ / ₁₆ "	300 x 604.8mm	2" (51mm)
12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	2 ³ / ₄ " (70mm)
			3 ⁷ / ₈ " (100mm)
8 x 8"	7 ⁷ / ₈ x 7 ⁷ / ₈ "	200 x 200mm	2 ³ / ₈ " (60mm)
			2 ³ / ₄ " (70mm)
4 x 8"	3 ⁷ / ₈ x 7 ⁷ / ₈ "	100 x 200mm	2 ³ / ₈ " (60mm)
			2 ³ / ₄ " (70mm)
			3 ¹ / ₈ " (80mm)
Load Lock™ - 12 x 24"	11 ⁷ / ₈ x 23 ⁵ / ₈ "	300x 600mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 6 x 12"	5 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	150 x 300mm	3 ⁷ / ₈ " (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 ⁷ / ₈ x 11 ⁷ / ₈ "	100 x 300mm	3 ⁷ / ₈ " (100mm)
Metro™ - 5 x 10"	5 x 10"	127 x 254mm	2 ³ / ₄ " (70mm)
Optiloc™	10 ¹ / ₄ x 10 ¹ / ₄ "	260 x 260mm	3 ¹ / ₈ " (80mm)
AnchorLock™	8 ⁷ / ₈ x 8 ⁷ / ₈ "	225 x 225mm	3 ¹ / ₈ " (80mm)
Metro™ Platform	5 x 10, 10 x 10, 10 x 15"	127 x 254, 254 x 254, 254 x 380mm	2 ³ / ₄ " (70mm)

CLASSIC

**PERMEABLE
SHAPES & SIZES**

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	9 ½ x 9 ½"	240 x 240mm	3 ⅞" (80mm)	7mm	4.6%
Eco-Priora™ - 5 x 10"	4 ¾ x 9 ½"	120 x 240mm	3 ⅞" (80mm)	7mm	6.8%
Eco-Priora™ - 5 x 5"	4 ¾ x 4 ¾"	120 x 120mm	3 ⅞" (80mm)	6mm	12.80%
Eco-Optiloc™	9 ⅞ x 9 ⅞"	250 x 250mm	3 ⅞" (80mm)	12mm	7.3%
DuraFlow®	9 ⅞ x 9 ⅞"	250 x 250mm	3 ⅞" (80mm)	12mm	8%
Turfstone™	15 ¾ x 23 ⅝"	400 x 600mm	3 ⅞" (80mm)	2mm	40%
Dura-Mat™	19 ¾ x 29 ¾"	500 x 500mm	3 ⅞" (100mm)	-	-
Eco-Line® Platform	3 ⅝ x 9 ⅜, 3 ⅝ x 11, 3 ⅝ x 12 ½, 3 ⅝ x 14, 4 ½ x 11, 4 ½ x 12 ½, 4 ½ x 14"	84 x 237, 84 x 277, 84 x 317, 84 x 357, 114 x 237, 114 x 277, 114 x 317, 114 x 357mm	3 ⅞" (100mm)	6.25mm	5.8%

CLASSIC

HEAVY-DUTY SHAPES & SIZES

STANDARD

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)
8 x 8"	7 ⁷ / ₈ x 7 ⁷ / ₈ "	200 x 200mm	2 ³ / ₄ " (70mm)
4 x 8"	3 ⁷ / ₈ x 7 ⁷ / ₈ "	100 x 200mm	2 ³ / ₄ " (70mm)
			3 ¹ / ₈ " (80mm)
Load Lock™ - 12 x 24"	11 ⁷ / ₈ x 23 ⁵ / ₈ "	300 x 600mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 6 x 12"	5 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	150 x 300mm	3 ⁷ / ₈ " (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 ⁷ / ₈ x 11 ⁷ / ₈ "	100 x 300mm	3 ⁷ / ₈ " (100mm)
Optiloc™	10 ¹ / ₄ x 10 ¹ / ₄ "	260 x 260mm	3 ¹ / ₈ " (80mm)
AnchorLock™	8 ⁷ / ₈ x 8 ⁷ / ₈ "	225 x 225mm	3 ¹ / ₈ " (80mm)

PERMEABLE

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	4 ³ / ₄ x 4 ³ / ₄ "	120 x 120mm	3 ¹ / ₈ " (80mm)	6mm	12.80%
Eco-Priora™ - 5 x 10"	4 ³ / ₄ x 9 ¹ / ₂ "	120 x 240mm	3 ¹ / ₈ " (80mm)	7mm	6.80%
Eco-Priora™ - 5 x 5"	9 ¹ / ₂ x 9 ¹ / ₂ "	240 x 240mm	3 ¹ / ₈ " (80mm)	7mm	4.6%
Eco-Optiloc™	9 ⁷ / ₈ x 9 ⁷ / ₈ "	250 x 250mm	3 ¹ / ₈ " (80mm)	12mm	7.3%
DuraFlow®	9 ⁷ / ₈ x 9 ⁷ / ₈ "	250 x 250mm	3 ¹ / ₈ " (80mm)	12mm	8%
Turfstone™	15 ³ / ₄ x 23 ⁵ / ₈ "	400 x 600mm	3 ¹ / ₈ " (80mm)	2mm	40%
Dura-Mat™	19 ³ / ₄ x 29 ³ / ₄ "	500 x 500mm	3 ⁷ / ₈ " (100mm)	-	-

CLASSIC

ROOF DECK SLAB SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
24 x 48"	23 ¹³ / ₁₆ x 47 ⁷ / ₈ "	604.8 x 1214.4mm	2 ¹ / ₂ " (63.5mm)
24 x 36" *Available with a false groove at 24"	23 ¹³ / ₁₆ x 35 ¹³ / ₁₆ "	604.8 x 909.6mm	2" (51mm)
24 x 24"	23 ¹³ / ₁₆ x 23 ¹³ / ₁₆ "	604.8 x 604.8mm	2" (51mm)
18 x 36"	17 ¹³ / ₁₆ x 35 ¹³ / ₁₆ "	452.4 x 909.6mm	2" (51mm)
18 x 24"	17 ¹³ / ₁₆ x 23 ¹³ / ₁₆ "	452.4 x 604.8mm	2" (51mm)
15 x 30"	15 x 29 ⁷ / ₈ "	375 x 750mm	2 ³ / ₈ " (60mm)
12 x 24"	11 ⁷ / ₈ x 23 ¹³ / ₁₆ "	300 x 604.8mm	2" (51mm)
Wind Uplift - 24 x 36" *Available with a false groove at 24"	23 ¹³ / ₁₆ x 35 ¹³ / ₁₆ "	604.8 x 909.6mm	2" (51mm)
Wind Uplift - 24 x 24"	23 ¹³ / ₁₆ x 23 ¹³ / ₁₆ "	604.8 x 604.8mm	2" (51mm)

CLASSIC

COLORS



STERLING



BEECHWOOD



SANDY BEIGE



CHAMOIS



RIVER (SRI 34 | SR 0.32)



SIERRA



AUTUMN RED



RUSTIC RED



TERRA COTTA



GRANITE



NATURAL (SRI 32 | SR 0.3)



SILVER GREY



CHARCOAL (SRI 9 | SR 0.12)

Colors may vary by plant of manufacture. Final product selection should be done with full size samples and mock-ups. Contact your Unilock Representative for details.

CLASSIC

TECHNOLOGIES, STANDARDS & LEED

TECHNOLOGIES

OPTIONAL: ClassicCoat™ - Factory Sealer for Thru-mix pavers

MANUFACTURING STANDARDS

Unilock meets and exceeds ASTM C936 - Standard Specification for Solid Concrete Interlocking Paving Units & C1782 - Standard Specification for Segmental Concrete Paving Slabs using test methods conforming to:

TYPE	ASTM	COMPRESSIVE STRENGTH	WATER ABSORPTION	FREEZE/THAW (49 CYCLES)	FLEXURAL STRENGTH	DIMENSIONAL ACCURACY
Pavers	ASTM C936	8,000 PSI MIN.	<5%	< 500 G/M2	-	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)
Slabs	ASTM C1782	8,000 PSI MIN.	<5%	< 500 G/M2	> 725 PSI AVG. > 650 PSI MIN.	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)

LEED CREDIT OPPORTUNITIES

Unilock products can help contribute to earning points toward LEED certification for your projects. See LEED v5 for more specific project site details when calculating credits.

LEED BD+C: New Construction	
Materials and Resources	Quantify and Assess Embodied Carbon
	Reduce Embodied Carbon Option 2. Environmental Product Declaration (EPD) Analysis
Sustainable Sites	Accessible Outdoor Space
	Enhanced Resilient Site Design
	Heat Island Reduction: Option 1. Nonroof and roof
	Rainwater Management: Option 1. Percentile of Rainfall Events*
LEED O+M: Existing Buildings	
Sustainable Sites	Heat Island Reduction: Option 1. Nonroof and roof

*Rainwater Management - Only contributes to LEED credit if permeable pavers are used.

SUPPORT

Your Unilock representative is here to support you at every stage of your project. Whether you need expert advice, product recommendations, or samples, we're just a call or click away.

Click [here](#) to connect with your representative or visit commercial.unilock.com/contact-us/