

# IL CAMPO<sup>®</sup>

## ARCHITECTURAL COLLECTION - PAVERS & SLABS

Created with technology exclusive to Unilock, the etched lines on the surface of Il Campo create a richly detailed and visually striking texture suitable for any application. These brushed lines enhance slip-resistance, making Il Campo ideal for plazas, walkways, and other high-traffic outdoor areas. Combining long-lasting durability with a contemporary architectural aesthetic, these pavers deliver both functional performance and exceptional visual appeal.



# IL CAMPO<sup>®</sup>

## STANDARD SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
36 x 36"	35 1/2 x 35 1/2"	900 x 900mm	3 7/8" (100mm)
24 x 24"	23 5/8 x 23 5/8"	600 x 600mm	2 3/8" (60mm)
			2 3/4" (70mm)
22 1/2 x 37 1/2"	22 1/2 x 37 3/8"	570 x 950mm	2 3/8" (60mm)
21 x 35 1/2"	21 1/4 x 35 1/2"	540 x 900mm	2 3/8" (60mm)
18 x 36"	17 3/4 x 35 1/2"	450 x 900mm	2 3/8" (60mm)
			3 7/8" (100mm)
18 x 24"	17 3/4 x 23 5/8"	450 x 600mm	2 3/8" (60mm)
16 x 16"	15 3/4 x 15 3/4"	400 x 400mm	2 3/4" (70mm)
			3 1/8" (80mm)
			3 7/8" (100mm)
15 x 30"	15 x 29 7/8"	375 x 750mm	2 3/8" (60mm)
12 x 24"	11 7/8 x 23 5/8"	300 x 600mm	2 3/4" (70mm)
			3 7/8" (100mm)
12 x 12"	11 7/8 x 11 7/8"	300 x 300mm	2 3/4" (70mm)
			3 7/8" (100mm)
9 x 9"	9 x 9"	228 x 228mm	2 3/8" (60mm)
8 x 24"	7 7/8 x 23 5/8"	200 x 600mm	2 3/4" (70mm)
			3 7/8" (100mm)
8 x 16"	7 7/8 x 15 3/4"	200 x 400mm	2 3/4" (70mm)
			3 7/8" (100mm)
8 x 8"	7 7/8 x 7 7/8"	200 x 200mm	2 3/8" (60mm)
			2 3/4" (70mm)
7 1/2 x 15"	7 1/2 x 15"	190 x 380mm	2 3/8" (60mm)
			3 1/8" (80mm)
7 x 14"	7 1/16 x 14 3/16"	180 x 360mm	2 3/8" (60mm)
			2 3/4" (70mm)
			3 1/8" (80mm)
6 x 24"	5 15/16 x 23 5/8"	150 x 600mm	2 3/4" (70mm)
6 x 12"	5 15/16 x 11 7/8"	150 x 300mm	2 3/4" (70mm)
			3 1/8" (80mm)
			3 7/8" (100mm)

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
6 x 6"	5 15/16 x 5 15/16"	150 x 150mm	2 3/4" (70mm)
4 x 16"	3 7/8 x 15 3/4"	100 x 400mm	2 3/4" (70mm)
			3 7/8" (100mm)
4 x 12"	3 7/8 x 11 7/8"	100 x 300mm	2 3/4" (70mm)
			3 7/8" (100mm)
4 x 8"	3 7/8 x 7 7/8"	100 x 200mm	2 3/8" (60mm)
			2 3/4" (70mm)
			3 1/8" (80mm)
3 x 12"	2 15/16 x 11 7/8"	75 x 300mm	3 7/8" (100mm)
2 3/8 x 9 1/2"	2 3/8 x 9 1/2"	60 x 240mm	2 3/8" (60mm)
			2 3/4" (70mm)
Load Lock™ - 12 x 24"	11 7/8 x 23 5/8"	300 x 600mm	3 7/8" (100mm)
Load Lock™ - 12 x 12"	11 7/8 x 11 7/8"	300 x 300mm	3 7/8" (100mm)
Load Lock™ - 6 x 12"	5 15/16 x 11 7/8"	150 x 300mm	3 7/8" (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 7/8 x 11 7/8"	100 x 300mm	3 7/8" (100mm)
Metro™ - 5 x 10"	5 x 10"	127 x 254mm	2 3/4" (70mm)
Trapezoid - 9 x 15"	9 x 15"	228 x 381mm	3 1/8" (80mm)
Hex™ - 8"	7 7/8 x 7 7/8"	200 x 200mm	2 3/4" (70mm)
Artline™ Platform	4 7/8 x 6 3/4, 4 7/8 x 10 3/8, 4 7/8 x 13 3/8, 4 7/8 x 17 3/4, 7 1/2 x 8 7/8, 7 1/2 x 13 3/8, 7 1/2 x 17 3/4"	125 x 169, 125 x 262.5, 125 x 337.5, 125 x 450, 187.5 x 225, 187.5 x 337.5, 187.5 x 450mm	2 3/4" (70mm)
Metro™ Platform	5 x 10, 10 x 10, 10 x 15"	127 x 254, 254 x 254, 254 x 380mm	2 3/4" (70mm)
Random Platform 1	7 1/2 x 15, 15 x 15, 15 x 22 1/2"	190 x 380, 380 x 380, 380 x 570mm	2 3/8" (60mm)
			3 1/8" (80mm)
Random Platform 2	7 x 14, 14 x 14, 14 x 21"	180 x 360, 360 x 360, 360 x 540mm	2 3/8" (60mm)
			3 1/8" (80mm)

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	9 ½ x 9 ½"	240 x 240mm	3 ⅛" (80mm)	7mm	4.6%
Eco-Priora™ - 5 x 10"	4 ¾ x 9 ½"	120 x 240mm	3 ⅛" (80mm)	7mm	6.8%
Eco-Priora™ - 5 x 5"	4 ¾ x 4 ¾"	120 x 120mm	3 ⅛" (80mm)	6mm	12.80%
Permeable - 12 x 12"	11 ⅞ x 11 ⅞"	150 x 600mm	3 ⅞" (100mm)	7mm	4.84%
Permeable - 6 x 24"	5 ⅙ x 23 ⅝"	150 x 600mm	2 ¾" (70mm)	10mm	6.23%
Permeable - 6 x 12"	5 ⅙ x 11 ⅞"	152.4 x 304.8mm	3 ⅛" (80mm)	10mm	10.65%
Permeable - 4 x 16"	3 ⅞ x 15 ¾"	100 x 400mm	3 ⅞" (100mm)	7mm	10.12%
Permeable - 4 x 12"	3 ⅞ x 11 ⅞"	100 x 300mm	3 ⅛" (80mm)	7mm	8.6%
Permeable - 3 x 12"	2 ⅙ x 11 ⅞"	75 x 300mm	3 ⅞" (100mm)	7mm	10.12%
Treo® - 4 ⅝ x 9 ¼"	4 ⅝ x 9 ¼"	116.5 x 233mm	2 ⅜" (60mm)	7mm	7.8%
Permeable Hex - 8"			2 ⅜" (60mm)	6.5mm	4.2%
			3 ⅛" (80mm)	10mm	4.2%
Eco-Optiloc™	9 ⅞ x 9 ⅞"	250 x 250mm	3 ⅛" (80mm)	12mm	7.3%
Treo® Platform	9 ¼ x 4 ⅝, 9 ¼ x 9 ¼, 9 ¼ x 13 ¾"	233 x 116, 233 x 233, 233 x 349mm	2 ⅜" (60mm)	7mm	5.5% avg.
			3 ⅛" (80mm)	7mm	5.5% avg.
Thornbury™ Platform	8 ¼ x 6 ⅞, 8 ¼ x 13 ¾, 13 ¾ x 16 ½"	210 x 173, 210 x 350, 350 x 420mm	2 ¾" (70mm)	11-18mm	7.7% avg.
Eco-Line® Platform	3 ⅙ x 9 ⅜, 3 ⅙ x 11, 3 ⅙ x 12 ½, 3 ⅙ x 14, 4 ½ x 11, 14 ½ x 12 ½, 4 ½ x 14"	84 x 237, 84 x 277, 84 x 317, 84 x 357, 114 x 237, 114 x 277, 114 x 317, 114 x 357mm	3 ⅞" (100mm)	6.25mm	5.8%

### STANDARD

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
12 x 12"	11 <sup>7</sup> / <sub>8</sub> x 11 <sup>7</sup> / <sub>8</sub> "	300 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
8 x 8"	7 <sup>7</sup> / <sub>8</sub> x 7 <sup>7</sup> / <sub>8</sub> "	200 x 200mm	2 <sup>3</sup> / <sub>4</sub> " (70mm)
6 x 12"	5 <sup>15</sup> / <sub>16</sub> x 11 <sup>7</sup> / <sub>8</sub> "	150 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
6 x 6"	5 <sup>15</sup> / <sub>16</sub> x 5 <sup>15</sup> / <sub>16</sub> "	150 x 150mm	2 <sup>3</sup> / <sub>4</sub> " (70mm)
4 x 12"	3 <sup>7</sup> / <sub>8</sub> x 11 <sup>7</sup> / <sub>8</sub> "	100 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
4 x 8"	3 <sup>7</sup> / <sub>8</sub> x 7 <sup>7</sup> / <sub>8</sub> "	100 x 200mm	2 <sup>3</sup> / <sub>4</sub> " (70mm)
			3 <sup>1</sup> / <sub>8</sub> " (80mm)
3 x 12"	2 <sup>15</sup> / <sub>16</sub> x 11 <sup>7</sup> / <sub>8</sub> "	75 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
3 x 6"	2 <sup>15</sup> / <sub>16</sub> x 5 <sup>15</sup> / <sub>16</sub> "	75 x 150mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
Load Lock™ - 12 x 24"	11 <sup>7</sup> / <sub>8</sub> x 23 <sup>5</sup> / <sub>8</sub> "	300 x 600mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
Load Lock™ - 12 x 12"	11 <sup>7</sup> / <sub>8</sub> x 11 <sup>7</sup> / <sub>8</sub> "	300 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
Load Lock™ - 6 x 12"	5 <sup>15</sup> / <sub>16</sub> x 11 <sup>7</sup> / <sub>8</sub> "	150 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 <sup>7</sup> / <sub>8</sub> x 11 <sup>7</sup> / <sub>8</sub> "	100 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)
Hex™ - 8"	7 <sup>7</sup> / <sub>8</sub> x 7 <sup>7</sup> / <sub>8</sub> "	200 x 200mm	2 <sup>3</sup> / <sub>4</sub> " (70mm)

### PERMEABLE

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	9 <sup>1</sup> / <sub>2</sub> x 9 <sup>1</sup> / <sub>2</sub> "	240 x 240mm	3 <sup>1</sup> / <sub>8</sub> " (80mm)	7mm	4.6%
Eco-Priora™ - 5 x 10"	4 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> "	120 x 240mm	3 <sup>1</sup> / <sub>8</sub> " (80mm)	7mm	6.80%
Eco-Priora™ - 5 x 5"	4 <sup>3</sup> / <sub>4</sub> x 4 <sup>3</sup> / <sub>4</sub> "	120 x 120mm	3 <sup>1</sup> / <sub>8</sub> " (80mm)	6mm	12.80%
Permeable - 12x 12"	11 <sup>7</sup> / <sub>8</sub> x 11 <sup>7</sup> / <sub>8</sub> "	300 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)	7mm	4.84%
Permeable - 3 x 12"	2 <sup>15</sup> / <sub>16</sub> x 11 <sup>7</sup> / <sub>8</sub> "	75 x 300mm	3 <sup>7</sup> / <sub>8</sub> " (100mm)	7mm	10.12%
Permeable Hex - 8"	8 <sup>1</sup> / <sub>16</sub> x 8 <sup>1</sup> / <sub>16</sub> "	205 x 205mm	2 <sup>3</sup> / <sub>8</sub> " (60mm)	6.5mm	4.2%
			3 <sup>1</sup> / <sub>8</sub> " (80mm)	10mm	4.2%

# IL CAMPO<sup>®</sup>

## ROOF DECK SLAB SHAPES & SIZES

SHAPE	ACTUAL SIZE (IMPERIAL)	ACTUAL SIZE (METRIC)	THICKNESS
22 ½ x 37 ½"	22 ½ x 37 ⅜"	570 x 950mm	2 ⅜" (60mm)
21 x 35 ½"	21 ¼ x 35 ½"	540 x 900mm	2 ⅜" (60mm)
21 x 35"	21 ¼ x 35 ⅛"	540 x 890mm	2 ⅜" (60mm)
18 x 36"	17 ¾ x 35 ½"	450 x 900mm	2 ⅜" (60mm)
18 x 24"	17 ¾ x 23 ⅝"	450 x 600mm	2 ⅜" (60mm)
15 x 30"	15 x 29 ⅞"	380 x 760mm	2 ⅜" (60mm)

# IL CAMPO<sup>®</sup>

## COLORS



**HERITAGE BROWN**



**SANDY BEIGE (SRI 19 | SR 0.2)**



**LIGHT GREY (SRI 22 | SR 0.22)**



**GRANITE**



**SS0381**



**DARK CHARCOAL**



**SS0287**



**SS0286**

Colors may vary by plant of manufacture. Final product selection should be done with full size samples and mock-ups. Contact your Unilock Representative for details.

### TECHNOLOGIES

**INCLUDED:** EnduraColor™ Face-mix

**OPTIONAL:** EasyClean™ Integral Factory Sealer

### MANUFACTURING STANDARDS

Unilock meets and exceeds ASTM C936 - Standard Specification for Solid Concrete Interlocking Paving Units & C1782 - Standard Specification for Segmental Concrete Paving Slabs using test methods conforming to:

TYPE	ASTM	COMPRESSIVE STRENGTH	WATER ABSORPTION	FREEZE/THAW (49 CYCLES)	FLEXURAL STRENGTH	DIMENSIONAL ACCURACY
Pavers	ASTM C936	8,000 PSI MIN.	<5%	<500 G/M2	-	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)
Slabs	ASTM C1782	8,000 PSI MIN.	<5%	<500 G/M2	> 725 PSI AVG. > 650 PSI MIN.	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)

### LEED CREDIT OPPORTUNITIES

Unilock products can help contribute to earning points toward LEED certification for your projects. See LEED v5 for more specific project site details when calculating credits.

LEED BD+C: New Construction	
Materials and Resources	Quantify and Assess Embodied Carbon
	Reduce Embodied Carbon Option 2. Environmental Product Declaration (EPD) Analysis
Sustainable Sites	Accessible Outdoor Space
	Enhanced Resilient Site Design
	Heat Island Reduction: Option 1. Nonroof and roof
	Rainwater Management: Option 1. Percentile of Rainfall Events*
LEED O+M: Existing Buildings	
Sustainable Sites	Heat Island Reduction: Option 1. Nonroof and roof

\*Rainwater Management - Only contributes to LEED credit if permeable pavers are used.

### SUPPORT

Your Unilock representative is here to support you at every stage of your project. Whether you need expert advice, product recommendations, or samples, we're just a call or click away.

Click [here](https://commercial.unilock.com/contact-us/) to connect with your representative or visit [commercial.unilock.com/contact-us/](https://commercial.unilock.com/contact-us/)