

SERIES™

ARCHITECTURAL COLLECTION - PAVERS & SLABS

Series pavers feature an exposed aggregate surface composed of natural granite and quartz, offering a bold, distinctive finish and a speckled color palette that enhances over time when exposed to outdoor elements. These pavers provide long-lasting durability and slip-resistance, making them ideal for a wide range of applications, including plazas, walkways, and streetscapes.



SERIES™

STANDARD SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
36 x 36"	35 1/2 x 35 1/2"	900 x 900mm	3 7/8" (100mm)
24 x 24"	23 5/8 x 23 5/8"	600 x 600mm	2 3/8" (60mm)
			2 3/4" (70mm)
22 1/2 x 37 1/2"	22 1/2 x 37 3/8"	570 x 950mm	2 3/8" (60mm)
21 x 35 1/2"	21 1/4 x 35 1/2"	540 x 900mm	2 3/8" (60mm)
18 x 36"	17 3/4 x 35 1/2"	450 x 900mm	2 3/8" (60mm)
			3 7/8" (100mm)
18 x 24"	17 3/4 x 23 5/8"	450 x 600mm	2 3/8" (60mm)
16 x 16"	15 3/4 x 15 3/4"	400 x 400mm	2 3/4" (70mm)
			3 1/8" (80mm)
			3 7/8" (100mm)
15 x 30"	15 x 29 7/8"	375 x 750mm	2 3/8" (60mm)
12 x 24"	11 7/8 x 23 5/8"	300 x 600mm	2 3/4" (70mm)
			3 7/8" (100mm)
12 x 12"	11 7/8 x 11 7/8"	300 x 300mm	2 3/4" (70mm)
			3 7/8" (100mm)
9 x 9"	9 x 9"	228 x 228mm	2 3/8" (60mm)
8 x 24"	7 7/8 x 23 5/8"	200 x 600mm	2 3/4" (70mm)
			3 7/8" (100mm)
8 x 16"	7 7/8 x 15 3/4"	200 x 400mm	2 3/4" (70mm)
			3 7/8" (100mm)
8 x 8"	7 7/8 x 7 7/8"	200 x 200mm	2 3/8" (60mm)
			2 3/4" (70mm)
7 1/2 x 15"	7 1/2 x 15"	190 x 380mm	2 3/8" (60mm)
			3 1/8" (80mm)
7 x 14"	7 1/16 x 14 3/16"	180 x 360mm	2 3/8" (60mm)
			2 3/4" (70mm)
			3 1/8" (80mm)
6 x 24"	5 15/16 x 23 5/8"	150 x 600mm	2 3/4" (70mm)
6 x 12"	5 15/16 x 11 7/8"	150 x 300mm	2 3/4" (70mm)
			3 1/8" (80mm)
			3 7/8" (100mm)

SERIES™

STANDARD SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
6 x 6"	5 15/16 x 5 15/16"	150 x 150mm	2 3/4" (70mm)
4 x 16"	3 7/8 x 15 3/4"	100 x 400mm	2 3/4" (70mm)
			3 7/8" (100mm)
4 x 12"	3 7/8 x 11 7/8"	100 x 300mm	2 3/4" (70mm)
			3 7/8" (100mm)
4 x 8"	3 7/8 x 7 7/8"	100 x 200mm	2 3/8" (60mm)
			2 3/4" (70mm)
			3 1/8" (80mm)
3 x 12"	2 15/16 x 11 7/8"	75 x 300mm	3 7/8" (100mm)
2 3/8 x 9 1/2"	2 3/8 x 9 1/2"	60 x 240mm	2 3/8" (60mm)
			2 3/4" (70mm)
Load Lock™ - 12 x 24"	11 7/8 x 23 5/8"	300 x 600mm	3 7/8" (100mm)
Load Lock™ - 12 x 12"	11 7/8 x 11 7/8"	300 x 300mm	3 7/8" (100mm)
Load Lock™ - 6 x 12"	5 15/16 x 11 7/8"	150 x 300mm	3 7/8" (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 7/8 x 11 7/8"	100 x 300mm	3 7/8" (100mm)
Metro™ - 5 x 10"	5 x 10"	127 x 254mm	2 3/4" (70mm)
Nordic Cobble™	3 5/8 x 3 3/4"	89.9 x 94mm	2 3/8" (60mm)
Trapezoid - 9 x 15"	9 x 15"	228 x 381mm	3 1/8" (80mm)
Hex™ - 8"	7 7/8 x 7 7/8"	200 x 200mm	2 3/4" (70mm)
Optiloc™	10 1/4 x 10 1/4"	260 x 260mm	3 1/8" (80mm)
Artline™ Platform	4 7/8 x 6 3/4, 4 7/8 x 10 3/8, 4 7/8 x 13 3/8, 4 7/8 x 17 3/4, 7 1/2 x 8 7/8, 7 1/2 x 13 3/8, 7 1/2 x 17 3/4"	125 x 169, 125 x 262.5, 125 x 337.5, 125 x 450, 187.5 x 225, 187.5 x 337.5, 187.5 x 450mm	2 3/4" (70mm)
Metro™ Platform	5 x 10, 10 x 10, 10 x 15"	127 x 254, 254 x 254, 254 x 380mm	2 3/4" (70mm)
Random Platform 1	7 1/2 x 15, 15 x 15, 15 x 22 1/2"	190 x 380, 380 x 380, 380 x 570mm	2 3/8" (60mm)
			3 1/8" (80mm)
Random Platform 2	7 x 14, 14 x 14, 14 x 21"	180 x 360, 360 x 360, 360 x 540mm	2 3/8" (60mm)
			3 1/8" (80mm)
Tribeca Cobble™ Platform	5 x 6 7/8, 5 x 9, 5 x 12"	130 x 175, 130 x 230, 130 x 305mm	2 3/4" (70mm)

SERIES™

PERMEABLE SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	9 1/2 x 9 1/2"	240 x 240mm	3 1/8" (80mm)	7mm	4.6%
Eco-Priora™ - 5 x 10"	4 3/4 x 9 1/2"	120 x 240mm	3 1/8" (80mm)	7mm	6.8%
Eco-Priora™ - 5 x 5"	4 3/4 x 4 3/4"	120 x 120mm	3 1/8" (80mm)	6mm	12.80%
Permeable - 12 x 12"	11 7/8 x 11 7/8"	150 x 600mm	3 7/8" (100mm)	7mm	4.84%
Permeable - 6 x 24"	5 15/16 x 23 5/8"	150 x 600mm	2 3/4" (70mm)	10mm	6.23%
Permeable - 6 x 12"	5 15/16 x 11 7/8"	152.4 x 304.8mm	3 1/8" (80mm)	10mm	10.65%
Permeable - 4 x 16"	3 7/8 x 15 3/4"	100 x 400mm	3 7/8" (100mm)	7mm	10.12%
Permeable - 4 x 12"	3 7/8 x 11 7/8"	100 x 300mm	3 1/8" (80mm)	7mm	8.6%
Permeable - 3 x 12"	2 15/16 x 11 7/8"	75 x 300mm	3 7/8" (100mm)	7mm	10.12%
Treo® - 4 5/8 x 9 1/4"	4 5/8 x 9 1/4"	116.5 x 233mm	2 3/8" (60mm)	7mm	7.8%
Permeable Hex - 8"			2 3/8" (60mm)	6.5mm	4.2%
			3 1/8" (80mm)	10mm	4.2%
Nordic Cobble™	3 5/8 x 3 3/4"	89.9 x 94mm	2 3/8" (60mm)	-	-
Eco-Optiloc™	9 7/8 x 9 7/8"	250 x 250mm	3 1/8" (80mm)	12mm	7.3%
Treo® Platform	9 1/4 x 4 5/8, 9 1/4 x 9 1/4, 9 1/4 x 13 3/4"	233 x 116, 233 x 233, 233 x 349mm	2 3/8" (60mm)	7mm	5.5% avg.
			3 1/8" (80mm)	7mm	5.5% avg.
Thornbury™ Platform	8 1/4 x 6 7/8, 8 1/4 x 13 3/4, 13 3/4 x 16 1/2"	210 x 173, 210 x 350, 350 x 420mm	2 3/4" (70mm)	11-18mm	7.7% avg.
Eco-Line® Platform	3 5/16 x 9 3/8, 3 5/16 x 11, 3 5/16 x 12 1/2, 3 5/16 x 14, 4 1/2 x 11, 14 1/2 x 12 1/2, 4 1/2 x 14"	84 x 237, 84 x 277, 84 x 317, 84 x 357, 114 x 237, 114 x 277, 114 x 317, 114 x 357mm	3 7/8" (100mm)	6.25mm	5.8%
Tribeca Cobble™ Platform	5 x 6 7/8, 5 x 9, 5 x 12"	130 x 175, 130 x 230, 130 x 305mm	2 3/4" (70mm)	9-15mm	5.6% avg.

SERIES™

HEAVY-DUTY SHAPES & SIZES

STANDARD

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)
8 x 8"	7 ⁷ / ₈ x 7 ⁷ / ₈ "	200 x 200mm	2 ³ / ₄ " (70mm)
6 x 12"	5 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	150 x 300mm	3 ⁷ / ₈ " (100mm)
6 x 6"	5 ¹⁵ / ₁₆ x 5 ¹⁵ / ₁₆ "	150 x 150mm	2 ³ / ₄ " (70mm)
4 x 12"	3 ⁷ / ₈ x 11 ⁷ / ₈ "	100 x 300mm	3 ⁷ / ₈ " (100mm)
4 x 8"	3 ⁷ / ₈ x 7 ⁷ / ₈ "	100 x 200mm	2 ³ / ₄ " (70mm)
			3 ¹ / ₈ " (80mm)
3 x 12"	2 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	75 x 300mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 12 x 24"	11 ⁷ / ₈ x 23 ⁵ / ₈ "	300 x 600mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 12 x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)
Load Lock™ - 6 x 12"	5 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	150 x 300mm	3 ⁷ / ₈ " (100mm)
			6" (150mm)
Load Lock™ - 4 x 12"	3 ⁷ / ₈ x 11 ⁷ / ₈ "	100 x 300mm	3 ⁷ / ₈ " (100mm)
Hex™ - 8"	7 ⁷ / ₈ x 7 ⁷ / ₈ "	200 x 200mm	2 ³ / ₄ " (70mm)
Optiloc™	10 ¹ / ₄ x 10 ¹ / ₄ "	260 x 260mm	3 ¹ / ₈ " (80mm)

PERMEABLE

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS	JOINT SPACING	VOID PERCENTAGE
Eco-Priora™ - 10 x 10"	9 ¹ / ₂ x 9 ¹ / ₂ "	240 x 240mm	3 ¹ / ₈ " (80mm)	7mm	4.6%
Eco-Priora™ - 5 x 10"	4 ³ / ₄ x 9 ¹ / ₂ "	120 x 240mm	3 ¹ / ₈ " (80mm)	7mm	6.80%
Eco-Priora™ - 5 x 5"	4 ³ / ₄ x 4 ³ / ₄ "	120 x 120mm	3 ¹ / ₈ " (80mm)	6mm	12.80%
Permeable - 12x 12"	11 ⁷ / ₈ x 11 ⁷ / ₈ "	300 x 300mm	3 ⁷ / ₈ " (100mm)	7mm	4.84%
Permeable - 3 x 12"	2 ¹⁵ / ₁₆ x 11 ⁷ / ₈ "	75 x 300mm	3 ⁷ / ₈ " (100mm)	7mm	10.12%
Permeable Hex - 8"	8 ¹ / ₁₆ x 8 ¹ / ₁₆ "	205 x 205mm	2 ³ / ₈ " (60mm)	6.5mm	4.2%
			3 ¹ / ₈ " (80mm)	10mm	4.2%
Eco-Optiloc™	9 ⁷ / ₈ x 9 ⁷ / ₈ "	250 x 250mm	3 ¹ / ₈ " (80mm)	12mm	7.3%

SERIES™

ROOF DECK SLABS SHAPES & SIZES

SHAPE	LENGTH & WIDTH (IMPERIAL)	LENGTH & WIDTH (METRIC)	THICKNESS
24 x 24"	23 ⁵ / ₈ x 23 ⁵ / ₈ "	600 x 600mm	2 ³ / ₈ " (60mm)
22 ¹ / ₂ x 37 ¹ / ₂ "	22 ¹ / ₂ x 37 ³ / ₈ "	570 x 950mm	2 ³ / ₈ " (60mm)
21 x 35 ¹ / ₂ "	21 ¹ / ₄ x 35 ¹ / ₂ "	540 x 900mm	2 ³ / ₈ " (60mm)
18 x 36"	17 ³ / ₄ x 35 ¹ / ₂ "	450 x 900mm	2 ³ / ₈ " (60mm)
18 x 24"	17 ³ / ₄ x 23 ⁵ / ₈ "	450 x 600mm	2 ³ / ₈ " (60mm)
15 x 30"	15 x 29 ⁷ / ₈ "	375 x 750mm	2 ³ / ₈ " (60mm)

SERIES™

COLORS



GOLDEN TAN (SRI 45 | SR 0.4)



SS0121



SS0020



MOCHA BROWN



SS0341



GLACIER



PEPPERED GRANITE (SRI 42 | SR 0.38)



SS0454



SS0412 (SRI 64 | SR 0.56)



ARCTIC GREY (SRI 27 | SR 0.26)



SS0032 W2 (SRI 29 | SR 0.28)



MOUNTAIN MIST (SRI 29 | SR 0.28)




MINERAL ICE GREY



SS00447



ICE GREY (SRI 38 | SR 0.35)



SS0451



NORDIC STAR (SRI 10 | SR 0.14)



CRYSTALLINE BASALT



PLATINUM GREY



COBALT GREY



BLACK GRANITE

Colors may vary by plant of manufacture. Final product selection should be done with full size samples and mock-ups. Contact your Unilock Representative for details.

UNILOCK®

SERIES™

TECHNOLOGIES, STANDARDS & LEED

TECHNOLOGIES

INCLUDED: EnduraColor™ Face-mix

MANUFACTURING STANDARDS

Unilock meets and exceeds ASTM C936 - Standard Specification for Solid Concrete Interlocking Paving Units & C1782 - Standard Specification for Segmental Concrete Paving Slabs using test methods conforming to:

TYPE	ASTM	COMPRESSIVE STRENGTH	WATER ABSORPTION	FREEZE/THAW (49 CYCLES)	FLEXURAL STRENGTH	DIMENSIONAL ACCURACY
Pavers	ASTM C936	8,000 PSI MIN.	<5%	<500 G/M2	-	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)
Slabs	ASTM C1782	8,000 PSI MIN.	<5%	<500 G/M2	> 725 PSI AVG. > 650 PSI MIN.	L&W: ± 1/16" (1.6mm) H: ± 1/8" (3.18mm)

LEED CREDIT OPPORTUNITIES

Unilock products can help contribute to earning points toward LEED certification for your projects. See LEED v5 for more specific project site details when calculating credits.

LEED BD+C: New Construction	
Materials and Resources	Quantify and Assess Embodied Carbon
	Reduce Embodied Carbon Option 2. Environmental Product Declaration (EPD) Analysis
Sustainable Sites	Accessible Outdoor Space
	Enhanced Resilient Site Design
	Heat Island Reduction: Option 1. Nonroof and roof
	Rainwater Management: Option 1. Percentile of Rainfall Events*
LEED O+M: Existing Buildings	
Sustainable Sites	Heat Island Reduction: Option 1. Nonroof and roof

*Only contributes to LEED credit if permeable pavers are used.

SUPPORT

Your Unilock representative is here to support you at every stage of your project. Whether you need expert advice, product recommendations, or samples, we're just a call or click away.

Click [here](#) to connect with your representative or visit commercial.unilock.com/contact-us/